



TELESCOPIC ARTICULATED LOADERS

608T ▶ 708T



KEY FEATURES

- ▲ 4-Post Canopy ROPS and FOPS Certified
- ▲ Cabin with Heat and Air Conditioning*
- ▲ Proportional Auxiliary Hydraulics with Case Drain and Circuit Pressure Dump
- ▲ Inching Pedal
- ▲ Digital Display with Audible and Visual Indicators
- ▲ Differential Lock (Hydraulically Activated Front and Rear)
- ▲ Power-A-Tach® Attachment Mounting System (4-Point, Skid Steer and EuroStyle)
- ▲ Telescopic Lift Arm with Z-Bar Loader Linkage with Mechanical Self-Level
- ▲ Lift Arm Float Detent
- ▲ 3-Speed*
- ▲ Hydraglide™ Ride Control*
- ▲ High-Flow Auxiliary Hydraulics*

*Optional features

TELESCOPIC ARTICULATED LOADERS

608T ▶ 708T

STANDARD FEATURES

- ▲ 4-Post Canopy ROPS and FOPS Certified
- ▲ Proportional Auxiliary Hydraulics with Case Drain and Circuit Pressure Dump
- ▲ Hydrostatic 2-Speed Transmission
- ▲ Lift Arm Float Detent
- ▲ Inching Pedal
- ▲ Electronic Hand Throttle
- ▲ Digital Display with Audible and Visual Indicators
- ▲ Steering Column with Tilt and Extension Adjustments
- ▲ Cup Holder
- ▲ Differential Lock (Hydraulically Activated Front and Rear)
- ▲ Oscillating Front Frame
- ▲ Rubber Floor Mat
- ▲ Power-A-Tach® Attachment Mounting System (EuroStyle, 4-Point & Skid Steer)
- ▲ Adjustable Arm Rest
- ▲ Seven-Way Adjustable Seat
- ▲ 12-Volt Socket in Arm Rest
- ▲ Telescopic Lift Arm with Z-Bar Loader Linkage with Mechanical Self-Level
- ▲ Multi-Function Joystick
- ▲ Lift / Tilt Electronic Lockout Switch
- ▲ Reverse and Brake Tail Lights
- ▲ Master Electrical Disconnect Switch
- ▲ Articulation Locking Bar (conforms to SAEJ276)
- ▲ Horn
- ▲ Side View Mirrors
- ▲ Front, Rear & Boon Worklights

OPTIONAL FEATURES

- ▲ 4-Post Canopy with Front and Rear Windows
- ▲ Cabin with Heat
- ▲ Cabin with Heat and Air Conditioning
- ▲ 3-Speed - **608T** 7 / 12 / 19 mph (11 / 20 / 30 km/hr)
708T 5 / 12 / 19 mph (8 / 20 / 30 km/hr)
- ▲ Seven-Way Adjustable Air Suspension Seat with or without Sewn Cushions
- ▲ LED Work Lights
- ▲ Speed Control
- ▲ Back-up Alarm
- ▲ Hydraglide™ Ride Control
- ▲ Rear Auxiliary Hydraulics
- ▲ Additional Set of Front Auxiliary Hydraulics
- ▲ High-Flow Auxiliary Hydraulics
- ▲ Radio (Bluetooth Hands-Free)
- ▲ Rotating Beacon
- ▲ Strobe Light
- ▲ Lockable Tool Box
- ▲ Engine Block Heater
- ▲ Side View Mirrors
- ▲ Front and Rear 12-Volt Electric Auxiliary
- ▲ License Plate Holder
- ▲ Electric Attachment Control 14-Pin Harness with Switches
- ▲ Rear Hitch - Clevis or Receiver
- ▲ 3 inch (75 mm) Seatbelt

SPECIFICATIONS

		608T	708T
DIMENSIONS	Height to Top of Cab / ROPS (mm)	8' 1" (2467)	8' 2" (2476)
	Width over Tires (mm)	5' 5" (1645)	6' 5" (1957)
	Length with Bucket on Ground (mm)	17' 10" (5433)	18' 10" (5730)
	Bucket Hinge Pin Height Retracted (mm)	11' 5" (3470)	12' 10" (3911)
	Bucket Hinge Pin Height Extended (mm)	14' 0" (4275)	16' 6" (5036)
	Maximum Dump Angle at Full Height	45°	45°
	Outer Turning Radius (mm)	12' 7" (3840)	13' 3" (4030)
	Articulation Angle from Center	40°	40°
	CAPACITIES	Static Tipping Load with Bucket Retracted (kg)	6,641 lbs. (3012)
Static Tipping Load with Bucket Extended (kg)		3,808 lbs. (1727)	4,071 lbs. (1846)
Bucket Breakout (kg)		11,004 lbs. (4990)	10,052 lbs. (4990)
Operating Weight with Bucket (kg)		10,460 lbs. (4745)	12,220 lbs. (5543)
ENGINE	Engine Manufacturer	Yanmar	Deutz
	Model / Number of Cylinders	4TNV98CT / 4	TD 3.6 L / 4
	Gross Power @ 2300 rpm (kW)	65 hp (49)	74 hp (55)
	Displacement (L)	202 cu in. (3.3)	220 cu in. (3.6)
HYDRAULICS	Work Hydraulic System Flow (L/min)	18.4 gpm (70)	18.4 gpm (70)
	Drive Hydraulic System Pressure (bar)	6,100 psi (420)	5,500 psi (380)
	Drive Hydraulic Reservoir Capacity (L)	19.5 gal. (73.7)	19.5 gal. (73.7)
OTHER	Travel Speeds (km/hr)	7/12 mph (11/20)	5/12 mph (8/20)
	Battery	12 V	12 V
	Fuel Tank Capacity (L)	20 gal. (77)	30 gal. (115)
	Tires	405 / 70 20	405 / 70 20

SPECIFICATIONS ARE PRELIMINARY

Mustang reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.

Mustang reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.



MUSTANG MFG.

147 Indiana Avenue, West Bend, WI 53095

Phone: (262) 334-9461